

Product family datasheet

Technical data

Electrical data


Product description	Nominal input voltage	Nominal output voltage	Nominal output power	Galvanic isolation
OT DIM	10...24 V	10.5...24 / 10.5...24 V	120 W	SELV equivalent

Dimensions & weight

Product description	Mounting hole spacing, length	Mounting length	Product weight	Cable cross-section, input side	Cable cross-section, output side
OT DIM	164.0 mm	164.0 mm	81.00 g	0.5...1.5 mm ²	0.5...1.5 mm ²

Product description	Wire preparation length, input side	Wire preparation length, output side	Width	Height	Length
OT DIM	10 mm	10 mm	42.0 mm	20.0 mm	172.0 mm

Product line drawing



OT DIM

Product family datasheet

Colors & materials

Product description	Casing material
OT DIM	Plastic

Temperatures & operating conditions

Product description	Ambient temperature range	Maximum temperature at tc test point	Temperature range at storage	Permitted rel. humidity during operation
OT DIM	-20...+50 °C	70 °C	-25...85 °C	5...85 % ¹⁾

¹⁾ Maximum 56 days/year at 85 %

Lifespan

Product description	ECG lifetime
OT DIM	50000 h

Capabilities

Product description	Dimmable	Dimming interface	Dimming range	Dimming method
OT DIM	Yes	1...10 V	0...100 %	Amplitude Modulation / Pulse Width Modulation

Product description	Overheating protection	Overload protection	Short-circuit protection	No-load proof
OT DIM	Automatic reversible ¹⁾	Automatic reversible ¹⁾	Automatic reversible ¹⁾	Yes

Product description	Suitable for fixtures with prot. class	Type of connection, output side
OT DIM	II	Screw terminal

¹⁾ In combination with OPTOTRONIC power supply

Certificates & standards

Product description	Approval marks – approval	Standards	Type of protection
OT DIM	CE / VDE / VDE-EMC	Acc. to DIN VDE 0875/CISPR 15/EN 55015/Acc. to EN 61547/Acc. to EN 55015/Acc. to EN 61547/Acc. to EN 61046/Acc. to IEC 61347-2-2/Acc. to UL 508	IP20

Product family datasheet

Logistical data

Product description	Commodity code
OT DIM	85371098990

Environmental information
Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)

Product description	Date of Declaration	Primary Article Identifier	Candidate List Substance 1
OT DIM	21-07-2023	4050300943459	Lead
Product description	CAS No. of substance 1	Safe Use Instruction	Declaration No. in SCIP database
OT DIM	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	b313a0eb-623a-448c-a191-430b12caefba

Application advice

For more detailed application information and graphics please see product datasheet.

Sales and Technical Support

Sales and Technical Support www.osram.com

Country specific information

Product description	Product code	METEL code	SEG-No.	STK number	UK Org
OT DIM	4050300943459	OSROTDIM	-	4031170	-
OT DIM	4050300943459	OSROTDIM	-	4031170	-

Download Data

File	
	Addon Technical Information 313229_ADDON TECHNICAL INFORMATION OT DIM VS20 OSRAM (GB)
	Brochures OPTOTRONIC constant-voltage LED power supplies and controls (EN)
	Certificates OT DIM 10 24 VDE ENEC 40027477 190422

Product family datasheet

	Declarations of conformity 334844_Declaration of conformity – OT Dimmer – OT Sequencer
	CAD data 3-dim OT DIM _ 3D igs file

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300943459	OT DIM	Shipping carton box 20	351 mm x 222 mm x 68 mm	5.30 dm³	2150.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.